

Ambuja

S O L V E X P V T. L T D.

(A Unit of Ambuja Intermediates Limited)

THE HERBAL MAGIC BY COLD PRESSED OILS

***“We are committed to produce and supply products
which help our bodies to maintain a true biological age
so we may live our full span of years with abundant
energy and goods health”***

Works

Survey No.: 1159, Opp. Sandvik Asia Ltd.
Village: Rajpur, Taluka: Kadi
District: Mehsana – 382 740 (North Gujarat), INDIA
Tel.: +91-2764-278403 / 278404, Fax: +91-2764-278415
Email: ailchatral@rediffmail.com

Registered Office

901-A, Narnarayan Complex
Swastik Cross Roads, Off C. G. Road
Navrangpura
Ahmedabad – 380 009 (Gujarat), INDIA
Tel.: +91-79-26427576 / 26427666
Fax: +91-79-26426694
Email: tradelink@icenet.co.in

Corporate / Export Divn Office

133, Bhandari Street
Null Bazar
Mumbai – 400 004 (Maharashtra), INDIA
Tel.: +91-22-23867792 / 23857141 /
23824143
Fax: +91-22-23809797
Email: ambuja@bom3.vsnl.net.in

COLD PRESSED CASTOR OIL



Cold Pressed Castor Oil is a pure virgin Water White Castor Oil extracted in its natural form just by pressing Seeds without subjecting the Seeds to any extreme condition so as to preserve its natural herbal and healing effects.

Castor Oil is regarded as one of the most valuable laxatives in medicine. It is of special service in temporary constipation and wherever a mild action is essential; and is extremely useful for children and aged. Castor Oil's natural healing qualities can be used for all inflammation.

However, it should be clearly noted that above effects are at its best and guaranteed if Cold Pressed Castor Oil is used; regular expeller or chemically extracted will not give the similar results.

**We have modern plant with traditional understanding to produce
100% natural "Cold Press Castor Oil"**

100% satisfaction guaranteed.

Packing Size: 50/100/200 Kgs. in a Food Grade Container or ISO-Container.

SPECIFICATION

Parameter	Observation
Appearance	Water White Clear Viscose Liquid
Odour	Natural Characteristic Odour
Colour Lovibond 5¼" Cell	10:Y 1:R
Acid Value	0.8 Max.
Peroxide Value	2 Max.
Iodine Value	85-90
Saponification Value	175-185
Moisture & Insoluble Impurities	0.5% Max.
Refractive Index @ 40°C	1.470-1.481
Specific Gravity @ 30°C / @ 30°C	0.952-0.965
Unsaponifiable	0.8% Max.
Light Absorption	Complies to BP

Note: Any other parameter can be given on request.

Applications : Pharmaceuticals / Cosmetics / Sports Flooring compounds / Light or Medium duty primers / Topcoats / Automotive Refinishes / Industrial Coatings / Wood Furniture / Teak Oil / Window Frames / Plastic : Hard PVC / Printing Inks / Polymers / Adhesives / Polyurethanes / Consumer Electronics / Lubrication & Metalworking / etc.